

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 October 2005 (27.10.2005)

PCT

(10) International Publication Number  
**WO 2005/099424 A2**

(51) International Patent Classification: Not classified

(21) International Application Number:  
PCT/US2005/003520

(22) International Filing Date: 28 January 2005 (28.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/539,834 28 January 2004 (28.01.2004) US

(71) Applicants and

(72) Inventors: EARLES, Ronald, B. [US/US]; 757 Kenrick Drive, Suite 124, Houston, TX 77060 (US) LASATER, Jeffrey, B. [US/US]; 757 Kenrick Drive, Suite 124, Houston, TX 77060 (US).

(74) Agent: ALWORTH, Charles, W.; Alworth Law and Engineering, 505 (Ex 502) Cumberland Road, Tyler, TX 75703-9325 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: ROTARY VECTOR GEAR FOR USE IN ROTARY STEERABLE TOOLS



(57) Abstract: A rotary vector gear for controlling longitudinal axis offset about a central longitudinal axis is disclosed. The device uses single rotary motion through a rotary vector gear to produce hypotrochoidic offset similar to a flower petal and is capable or ready return to zero offset. The device may be used in downhole rotary steerable oil and gas drilling tools and in computer controlled milling machines for providing controlled offset.

WO 2005/099424 A2



**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*